

OEM Recommended DPF/DOC Cleaning Intervals*

INTERNATIONAL

MaxxForce 5, 7, DT, 9-13

- **200,000 miles/ 6,500 hours** for on highway truck application.
- **75,000 miles/ 2,240 hours** for severe service application.

DETROIT DIESEL

DD13, DD15, DD16

- **300,000 miles/ 9,000 hours** for on highway truck application.
- **60,000 miles/ 2,000 hours** for severe service application.

CATERPILLAR

C-15, C-13, C-9, C-7

- **150,000 miles/ 4500 hours** for on highway truck application.
- **80,000 miles/ 2400 hours** for severe service application.

CUMMINS

ISB, ISC, ISL, ISM, ISX

- **200,000 miles/6,500 hours** for on highway truck application.
- **75,000 miles/ 2,420 hours** for severe service application.

ISUZU

4HK1-TC, 6HK1-TC

- **150,000 miles/ 4,500 hours**

HINO

J05D-TF, J08E-TV, J08E-TW

- **200,000 miles/ 6,500 hours**

PACCAR

PX-8, PX-6

- **200,000 miles/6,500 hours**

MACK

J05DT, J08EU

- **250,000 miles/ 4,500 hours**

* Based on engine make and model

VOLVO

J05DT, J08EU

- **150,000 miles/ 4,500 hours**

GMC

DURAMAX

- **120,000 miles** for the first service
- **Every 100,000 miles** afterwards